DEDAR
MILANO

FABRIC
ART. **BELSUELDE**
CAT. H

meli
HOME & CONTRACT

FABRIC
SAMPLES




BELSUEDE
001



BELSUEDE
002




BELSUEDE
003




BELSUEDE
004



BELSUEDE
005




BELSUEDE
006




BELSUEDE
007


BELSUEDE
008




BELSUEDE
009




BELSUEDE
010




BELSUEDE
011




BELSUEDE
012




BELSUEDE
013




BELSUEDE
014




BELSUEDE
015




BELSUEDE
016




BELSUEDE
017




BELSUEDE
018




BELSUEDE
019




BELSUEDE
022




BELSUEDE
023




BELSUEDE
025



BELSUEDE
027



BELSUEDE
029




BELSUEDE
030




BELSUEDE
031




BELSUEDE
032



BELSUEDE
033



BELSUEDE
034




BELSUEDE
035




BELSUEDE
036




BELSUEDE
037




BELSUEDE
038



BELSUEDE
039



BELSUEDE
040



BELSUEDE
041

DEDAR
MILANO

FABRIC
ART. **BELSUELDE**
CAT. H

COMPOSITION:	55% CV 30% LI 15% CO
WIDTH:	140 cm
WEIGHT:	810 G/ML
MARTINDALE:	20000 EN ISO 12947-2
LIGHTFASTNESS:	4/5 EN ISO 105-B02
PILLING:	4 5000 RUBS EN ISO 12945
FIRE RETARDANCY:	FR -Europe EN 1021 1&2

CARE:



WITH USE, THE PILE OF CHENILLE MAY SHOW A CRUSHED EFFECT, GIVING THIS FABRIC ITS “LIVED IN” LOOK WHICH MUST NOT BE CONSIDERED A FLAW BUT AN INTRINSIC AND UNIQUE CHARACTERISTIC. WHEN USED FOR UPHOLSTERY THE PILE TENDS TO CRUSH AND ALTER THE WAY IN WHICH IT REFLECTS THE LIGHT, CREATING A SHADING OR SHEEN DERIVING FROM USE. IN ORDER TO REFRESH IT AND REINVIGORATE THE PILE IT IS ADVISABLE TO BRUSH AND STEAM THE FABRIC AT A DISTANCE OF 30 CM. PLEASE NOTE THAT THE STEAM SHOULD NOT COME INTO DIRECT CONTACT WITH THE MATERIAL. BRUSHING SHOULD BE DONE BOTH IN VERTICAL AND HORIZONTAL WAY. WE RECOMMEND REPEATING THE PROCESS TILL THE VELVET RESUMES THE ORIGINAL APPEARANCE. WHENEVER USING BELSUEDE FOR UPHOLSTERY APPLICATIONS, IT IS ADVISABLE TO ADOPT STUFFING OR AN INNER LINING THAT CREATES FRICTION WITH THE FABRIC.

OEKO TEX® STANDARD 100
20CX00044
CENTROCOT